



Spartan Chemical Company, Inc.

1110 Spartan Drive, Maumee OH 43537

Phone: (800) 537-8990

www.spartanchemical.com

Training Information

Market Segment:

Building Service Contractors, Education, Food Processing_Agricultural, General Manufacturing, Government, Healthcare, Lodging_Hospitality, Other, Retail

Title:

HOW TO HIGH SPEED RESTORE A FLOOR

Check If Applicable: Rx Procedure None
 Cleancheck Procedure

Tools & Materials Needed:

- A. Finish mop
- B. Mop bucket with wringer
- C. Liner
- D. High speed machine
- E. Pads
- F. "Wet floor" signs
- G. Products
- H. Gloves and glasses

Products:

Floor finish restorer

Procedures:

I. Purpose of High Speed Restoration

- A. Restore luster to floor dulled by heavy foot traffic.
- B. Give the floor the "wet look".
- C. Used between recoating and stripping to fill in scratches.

II. Procedure for High Speed Restoration

- A. Allow floor to dry thoroughly after damp mopping.
- B. Line an empty mop bucket with a liner. Put on gloves and glasses.
- C. Mix floor finish restorer with water according to manufacturer's directions.
- D. Place or keep "Wet floor" signs at each entrance.
- E. Dip a clean finish mop into the floor finish restorer and wring out dry enough so it does not drip.

F. Apply a thin coat of floor restorer

1. Start in farthest corner from the entrance.
2. Apply in figure eight motion, in 6 to 8 foot sections.
3. Turn mop head over frequently.

G. Allow to dry while cleaning up equipment.

1. Clean out finish mop.
2. Discard any floor finish restorer remaining in bucket. Twist, tie and toss.

H. Dry buff the floor finish restorer on the floor using a high speed machine with the appropriate pad.

I. After polishing floor, wash out pads. Store all equipment away for future use.